FICHE TECHNIQUE Code: 502326 17-09-2020

FORK MIXER 2330 MEB





70 rue Anne de Bretagne - PA des Marches de Bretagne Saint-Hilaire-de-Loulay - 85600 Montaigu Vendée Tél. : + 33 (0)2 51 45 35 35 – Fax : + 33 (0)2 51 06 40 84 comm-ind@vmi.fr

Lift head high: 2400 mm Depth: 2040 mm Width: 1680 mm



CONFORMITY

- With the directive Machines 2006/42 CE
- With the directive EMC 2004/108 CE
- With the directive Low voltage electrical equipment 2006/95 CE
- With the norm EN 453

ELECTRIC FEATURES

• Power supply: tri 400 V - 50 Hz + Ground

Control circuit voltage: 24 VAC

• Installed power: 5.5 kW

IP54

Feeding wire 4 meters

GENERAL FEATURES

- Bowl capacity: around 330 litres
- Unloaded kneader weight: around 1500 kg
- Tool speed: around 52 and 78 rpm
- Noise level: <70 dBA (PREN31201)
- Dough quantity:
 - Max: 160 kg with 60% of water
 - min: 55 kg with 60% of water
- Safety grid with front opening
- Manual locking bowl
- · hydraulic lifting of the head
- Bowl, braked

SECURITY

- · Bowl safety grid
- Safety fence

CONSTRUCTION

FRAME

- · Frame in welded mechanical steel, grey paint
- Base on pin under column

BOWL

In aluminium AS12

TOOL

• Fork in aluminium AS7G

GRID

• Grid in steel

CONTROL PANEL

Control panel with:

- 2 timers
- 1 stop button
- 1 cycle switch
- 1 tool high speed button
- 1 tool small speed button
- 1 cycle suspension button
- 1 head dlifting button
- 1 head lowering button
- 1 bowl lifting button
- 1 bowl lowering button

OPTIONS

- Other tension and frequency: call us
- Bowl in stainless steel
- Grid in stainless steel with stitch or plain
- Bowl top cover in stainless steel
- Frame in stainless steel
- Fork in stainless steel 2 or 3 arms
- Fork in aluminium 3 arms
- Bowl driven